

TP-LINK HX520 (2-PACK) MESH TEKNİK ÖZELLİKLER

DONANIM ÖZELLİKLERİ

| | |
|------------------------------|--|
| Arabirim | 3× Gigabit Ports *Per Unit 1 Port supports WAN/LAN auto-sensing |
| Buton | Reset Button WPS Button |
| Harici Güç Kaynağı | 12 V = 1.5 A |
| Boyutlar (W X D X H) | 4.7 x 4.7 x 3.8 in (120 x 120 x 96.5 mm) |

KABLOSUZ ÖZELLİKLERİ

| | |
|-------------------------|--|
| Kablosuz Standartlar | Wi-Fi 6 IEEE 802.11a/n/ac/ax 5 GHz IEEE 802.11b/g/n/ax 2.4 GHz |
| Frekans | 2.4 GHz and 5 GHz |
| Bağlantı Hızı | AX3000 5 GHz: Up to 2402 Mbps (HE160) 2.4 GHz: Up to 574 Mbps (HE40)* |

KABLOSUZ ÖZELLİKLERİ

| | |
|-------------------|--|
| Kablosuz Güvenlik | WPA/WPA2/WPA3 Personal encryptions |
| İletim Gücü | CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz) |
| Çoklu-SSID | 2× 5 GHz Multi-SSID 2× 2.4 GHz Multi-SSID |

YAZILIM ÖZELLİKLERİ

| | |
|---------------------|---|
| Mesh Technology | EasyMesh compatible, and supports 802.11k/v/r and Ethernet backhaul |
| Quality of Service | WMM |
| Gelişmiş Özellikler | Parental Controls, QoS (Quality of Service), Address Reservation, Port Forwarding, WiFi Schedule |
| WAN Türü | Dynamic IP/Static IP/PPPoE |
| Yönetim | Local management: WebGUI, Aginet app (for end users) Remote management: TR-069, TR-098, TR- 181, TR-369, TR- 111, TR-143 for service providers |

YAZILIM ÖZELLİKLERİ

| | |
|--------------------|--|
| | <p>Aginet App for end users (need to log in with TP-Link ID and bind your device to it)</p> <p>Cloud management: TP-Link Aginet Unified Cloud (TAUC)</p> |
| Firewall Güvenliđi | SPI Firewall |
| Protokoller | IPv4 IPv6 |
| Working Modes | Router Mode Access Point Mode |

DİĐERLERİ

| | |
|--------------|---|
| Paket İeriđi | <p>HX520 (2-pack) 2 HX520 Units 1 RJ45 Ethernet Cable 2 Power Adapters 1 Quick Installation Guide</p> <p>HX520 (1-pack) 1 HX520 Unit 1 RJ45 Ethernet Cable 1 Power Adapter 1 Quick Installation Guide</p> |
| Sertifikalar | CE |

DIĐERLERİ

| | |
|-------|--|
| Ortam | Operating Temperature: 0°C-40°C (32°F-104°F) Storage Temperature: - 40°C-60°C (-40°F- 140°F) Operating Humidity: 10%-90% non- condensing Storage Humidity: 5%- 90% non-condensing |
|-------|--|